



640_{px}
THERMAL
RESOLUTION

30_{mK}
SENSITIVITY

60_{Hz}
FRAME RATE

**INTEL
FPGA**

**ONVIF
RTSP**



WORKSWELL WEOM ETHERNET (POE) ITAR-FREE THERMAL IMAGING CAMERA CORE

Datasheet

Release date: 5th of February 2026

Version: 260205

WEOM Smart Ethernet thermal imaging core

WEOM thermal imaging camera core key features description

ITAR-free thermal imaging camera module designed and produced in Europe with unmatched quality suitable for all types of demanding applications such as unmanned vehicle (UAV/UGV), thermal monocular/binocular, thermal fixed industrial and security cameras, maritime thermal cameras, machine vision thermal cameras, monitoring and intelligent systems, driving systems, defense, security and many more.

Advanced FPGA processing provides outstanding image quality and scene visualization with high performance **sensitivity of 30mK and resolution of the detector 640 x 480 px**. WEOM offers small dimensions, weight, variety of lenses and exchangeable interfaces (HDMI, CVBS, USB, CMOS, GigE, Smart Ethernet) for integrators.

Technical specification

Detector type	Uncooled LWIR detector, microbolometer
Spectral band	8 – 14 μm
Detector resolution	640 x 480 px
Detector pixel size	17 μm (up to 30% higher sensitivity than 12 μm detector)
Detector sensitivity	<30 mK or <50 mK
Image frame rate	9 Hz, 30 Hz or 60 Hz full frame rate
Scene temperature range	High Gain mode up to +150 °C, Low Gain mode up to +550 °C High Gain mode up to +302 °F, Low Gain mode up to +1 022 °F
Non-uniformity correction (NUC)	Integrated, factory calibrated
Fixed focus lenses (M25)	FOV 42° (H) x 32° (V), focal length 14 mm, f/1.2 FOV 24° (H) x 18° (V), focal length 25 mm, f/1.2 FOV 17° (H) x 13° (V), focal length 35 mm, f/1.1
Fixed focus lenses (M34)	FOV 90° (H) x 70° (V), focal length 7 mm, f/1.0 FOV 49° (H) x 36° (V), focal length 13 mm, f/1.0 FOV 32° (H) x 20° (V), focal length 19 mm, f/1.0 FOV 25° (H) x 19° (V), focal length 25 mm, f/1.0 FOV 19° (H) x 16° (V), focal length 35 mm, f/1.0 FOV 12° (H) x 9° (V), focal length 50 mm, f/1.2 FOV 10° (H) x 7° (V), focal length 60 mm, f/1.0 FOV 8° (H) x 6° (V), focal length 73 mm, f/1.05 FOV 6° (H) x 4° (V), focal length 100 mm, f/1.0
Lens-less delivery	WEOM is available in lens-less version (M25 or M34 lens holder)
Image orientation	Invert (Flip the image vertically), Mirror (Flip the image horizontally)
Control software	Control software WEOM GUI
Spatial image filter	Median full frame 60Hz spatial filter for improved image quality
Temporal image filters	Time-domain 2x, 4x moving average filter for improved image quality



AGC	Automatic Image Gain Control (Plateau Histogram equalization)
MGC	Manual Gain Control function (Brightness, Contrast)
Image palettes	14 image palettes available in total (2 definable by the user)
Digital zoom	1x, 2x, 4x digital zoom function
Dead Pixel Correction	User Dead Pixel correction wizard
Temperature drift compensation	Factory calibrated for temperature drift compensation
WEOM Smart Ethernet Video outputs and control	
Ethernet (PoE)	Ethernet, RJ45 (PoE), 1Gb/s (100Mb/s compatible) 2-pin power supply connector Harting 14110213001000 8-pin AUX connector Phoenix 1780837 (DI, DO, RS485, Termination)
Video stream via Ethernet	RTSP, H264 encoded video, real-time stream in web-client User definable video output data stream via API – Pre-IGC MONO 14-bit data or Post-IGC coloring data
Thermal core control via Ethernet	ONVIF supported for the third-party software inter-compatibility Web server camera interface ONVIF and web server is fully synchronized
PTZ control	PELCO D protocol via RS485 Baudrate and address configurable via webserver Relative and absolute positioning Continuous movement with speed control Presets
Network settings	Static IP or DHCP functionality MAC Address configuration HTTPS (importa self-signed/authority certificate)
User management	Login and password 3 different user roles
Remote update	Available via webserver, customized
Time to start	< 5 sec
Physical attributes	
Mounting holes	6 x M2 mounting holes
Dimensions (without lens)	92.5 mm (3.64 in) x 47.2 mm (1.85 in) x 46.1 mm (1.81 in)
Weight	< 170 g (5.99 oz) without the lens
Power supply	
Input voltage for Smart Ethernet	External 12-24 VDC or PoE (IEEE 802.3af) RJ45 connector
Power dissipation	Smart Ethernet plugin: Typically 6W, 7.5 W peak
Environmental data	
IP rating (Encapsulation)	IP67 (at front of lens)



Operating temperature	-32°C to +70°C (-25.6 °F to 158 °F) according to MIL standard
Storage temperature	-50°C to +90°C (-58 °F to 194 °F)
Humidity	5% to 95% non-condensing
Vibration	Operating Random Vibration Test 5-500Hz, 3.0Grms
Shock	Operating Shock Test 15G, 11ms duration
Housing material	Durable aluminum body
ROHS, REACH, WEEE, CE	Compliant



DRI information for WEOM lenses

The calculations are based on the “Johnson Criteria” that is used for DRI (Detection, Recognition, and Identification). According to the Johnson Criteria, the minimum resolution, pixels on target, required to achieve a 50% probability for an observer to discriminate an object are:

(D) Detection:

If a target is found in the field of view, the image of the target must account for more than 1.5 pixels in the critical dimension direction.

(R) Recognition:

The target is classified to identify whether the target is a car, truck or person, which means that the image of the target must occupy more than 6 pixels in the critical dimension direction.

(I) Identification:

The definition of identification is that the model and other characteristics of the target can be distinguished. The image of the target must occupy more than 12 pixels in the critical dimension direction.

Lens	Human (1.8 m x 0.5 m) (5.90 ft x 1.64 ft)			Vehicle (2.3 m x 2.3 m) (7.54 ft x 7.54 ft)			Drone (0.5 m x 0.5 m) (1.64 ft x 1.64 ft)		
	D	R	I	D	R	I	D	R	I
14 mm (M25)	520 m	130 m	70 m	1 260 m	320 m	160 m	270 m	70 m	30 m
25 mm (M25)	930 m	230 m	120 m	2 250 m	560 m	280 m	490 m	120 m	60 m
35 mm (M25)	1 300 m	330 m	160 m	3 160 m	790 m	390 m	690 m	170 m	90 m
7 mm (M34)	280 m	70 m	35 m	675 m	170 m	85 m	150 m	35 m	25 m
13 mm (M34)	480 m	120 m	60 m	1 170 m	290 m	150 m	250 m	60 m	30 m
19 mm (M34)	710 m	180 m	90 m	1 710 m	430 m	210 m	370 m	90 m	50 m
25 mm (M34)	930 m	230 m	120 m	2 250 m	560 m	280 m	490 m	120 m	60 m
35 mm (M34)	1 300 m	330 m	160 m	3 160 m	790 m	390 m	690 m	170 m	90 m
50 mm (M34)	1 860 m	470 m	230 m	4 510 m	1 130 m	560 m	980 m	250 m	120 m
60 mm (M34)	2 240 m	560 m	280 m	5 410 m	1 350 m	680 m	1 180 m	290 m	150 m
73 mm (M34)	2 720 m	680 m	340 m	6 580 m	1 650 m	820 m	1 430 m	360 m	180 m
100 mm (M34)	3 730 m	930 m	470 m	9 020 m	2 250 m	1 130 m	1 960 m	490 m	250 m

* Real values may vary based on environmental conditions and integration.



Contact information

WORKSWELL IN THE WORLD



Find our partners worldwide

www.workswell.eu/where-to-buy

SALES DEPARTMENT

Website: www.workswell.eu

E-mail: sales@workswell.eu

Mobile: +420 737 547 622

COMPANY CONTACT

Website: www.workswell.eu

E-mail: info@workswell.eu

Mobile: +420 725 877 063

OFFICE LOCATIONS

Europe - Prague

United States of America

Global partner network



www.workswell.eu