



**640px**  
THERMAL  
RESOLUTION

**30mK**  
SENSITIVITY

**60Hz**  
FRAME RATE

**INTEL  
FPGA**

**USB**



# WORKSWELL WEOM USB

## ITAR-FREE THERMAL IMAGING CAMERA CORE

## Datasheet

**Release date:** 15<sup>th</sup> of January 2026

**Version:** 260115

# WEOM USB thermal imaging core specification

## WEOM USB thermal imaging camera core key features description

**ITAR-free thermal imaging camera module designed and produced in Europe** with unmatched quality suitable for all types of demanding applications such as unmanned vehicle (UAV/UGV), thermal monocular/binocular, thermal fixed industrial and security cameras, maritime thermal cameras, machine vision thermal cameras, monitoring and intelligent systems, driving systems, defense, security and many more.

Advanced FPGA processing provides outstanding image quality and scene visualization with high performance **sensitivity of 30mK and resolution of the detector 640 x 480 px**. WEOM offers small dimensions, weight, variety of lenses and exchangeable interfaces (HDMI, CVBS, USB, CMOS, GigE, Smart Ethernet) for integrators.

## Technical specification

<b>Detector type</b>	Uncooled LWIR detector, microbolometer
<b>Spectral band</b>	8 – 14 $\mu\text{m}$
<b>Detector resolution</b>	640 x 480 px
<b>Detector pixel size</b>	17 $\mu\text{m}$ (up to 30% higher sensitivity than 12 $\mu\text{m}$ detector)
<b>Detector sensitivity</b>	<30 mK or <50 mK
<b>Image frame rate</b>	9 Hz, 30 Hz or 60 Hz full frame rate
<b>Scene temperature range</b>	High Gain mode up to +150 °C, Low Gain mode up to +550 °C High Gain mode up to +302 °F, Low Gain mode up to +1 022 °F
<b>Non-uniformity correction (NUC)</b>	Integrated, factory calibrated
<b>Fixed focus lenses (M25)</b>	FOV 42° (H) x 32° (V), focal length 14 mm, f/1.2 FOV 24° (H) x 18° (V), focal length 25 mm, f/1.2 FOV 17° (H) x 13° (V), focal length 35 mm, f/1.1
<b>Fixed focus lenses (M34)</b>	FOV 90° (H) x 70° (V), focal length 7 mm, f/1.0 FOV 49° (H) x 36° (V), focal length 13 mm, f/1.0 FOV 32° (H) x 20° (V), focal length 19 mm, f/1.0 FOV 25° (H) x 19° (V), focal length 25 mm, f/1.0 FOV 19° (H) x 16° (V), focal length 35 mm, f/1.0 FOV 12° (H) x 9° (V), focal length 50 mm, f/1.2 FOV 10° (H) x 7° (V), focal length 60 mm, f/1.0 FOV 8° (H) x 6° (V), focal length 73 mm, f/1.05 FOV 6° (H) x 4° (V), focal length 100 mm, f/1.0
<b>Lens-less delivery</b>	WEOM is available in lens-less version (M25 or M34 lens holder)
<b>Image orientation</b>	Invert (Flip the image vertically), Mirror (Flip the image horizontally)
<b>Control software</b>	Control software WEOM GUI
<b>Spatial image filter</b>	Median full frame 60Hz spatial filter for improved image quality
<b>Temporal image filters</b>	Time-domain 2x, 4x moving average filter for improved image quality



<b>AGC</b>	Automatic Image Gain Control (Plateau Histogram equalization)
<b>MGC</b>	Manual Gain Control function (Brightness, Contrast)
<b>Image palettes</b>	14 image palettes available in total (2 definable by the user)
<b>Dead Pixel Correction</b>	User Dead Pixel correction wizard
<b>Temperature drift compensation</b>	Factory calibrated for temperature drift compensation
<b>WEOM USB Video outputs and control</b>	
<b>USB plugin</b>	1x USB-C connector for video UVC output & power supply 1x JST connector for AUX signals Video format Pre-IGC MONO 14bit, Post-coloring YCbCr
<b>CMOS</b>	14-bit parallel video (50-pin Hirose), primary electronic interface
<b>Serial communication</b>	UART serial communication channel for WEOM control
<b>Time to start</b>	< 5 sec
<b>Physical attributes</b>	
<b>Mounting holes</b>	6 x M2 mounting holes
<b>Dimensions (CMOS version)</b>	40.1 (h) x 37.8 (w) x 42.6 (l) mm (1.57 x 1.48 x 1.67 in) without the lens
<b>Weight</b>	< 81.1 g (2.86 oz) including the USB plugin (without the lens)
<b>Power supply</b>	
<b>Input voltage</b>	4.8 to 5.2 VDC
<b>Primary electronic interface</b>	CMOS (50-pin Hirose)
<b>Power dissipation</b>	CMOS: Typically 1.9 W, 2.1 W peak USB: Typically 2.0 W, 2.2 W peak
<b>Environmental data</b>	
<b>IP rating (Encapsulation)</b>	IP67 (at front of lens)
<b>Operating temperature</b>	-32°C to +70°C (-25.6 °F to 158 °F) according to MIL standard
<b>Storage temperature</b>	-50°C to +90°C (-58 °F to 194 °F)
<b>Humidity</b>	5% to 95% non-condensing
<b>Vibration</b>	Operating Random Vibration Test 5-500Hz, 3.0Grms
<b>Shock</b>	Operating Shock Test 15G, 11ms duration
<b>Housing material</b>	Durable aluminum body
<b>ROHS, REACH, WEEE, CE</b>	Compliant



### DRI information for WEOM lenses

The calculations are based on the “Johnson Criteria” that is used for DRI (Detection, Recognition, and Identification). According to the Johnson Criteria, the minimum resolution, pixels on target, required to achieve a 50% probability for an observer to discriminate an object are:

**(D) Detection:**

If a target is found in the field of view, the image of the target must account for more than 1.5 pixels in the critical dimension direction.

**(R) Recognition:**

The target is classified to identify whether the target is a car, truck or person, which means that the image of the target must occupy more than 6 pixels in the critical dimension direction.

**(I) Identification:**

The definition of identification is that the model and other characteristics of the target can be distinguished. The image of the target must occupy more than 12 pixels in the critical dimension direction.

Lens	Human (1.8 m x 0.5 m) (5.90 ft x 1.64 ft)			Vehicle (2.3 m x 2.3 m) (7.54 ft x 7.54 ft)			Drone (0.5 m x 0.5 m) (1.64 ft x 1.64 ft)		
	D	R	I	D	R	I	D	R	I
<b>14 mm</b> (M25)	520 m	130 m	70 m	1 260 m	320 m	160 m	270 m	70 m	30 m
<b>25 mm</b> (M25)	930 m	230 m	120 m	2 250 m	560 m	280 m	490 m	120 m	60 m
<b>35 mm</b> (M25)	1 300 m	330 m	160 m	3 160 m	790 m	390 m	690 m	170 m	90 m
<b>7 mm</b> (M34)	280 m	70 m	35 m	675 m	170 m	85 m	150 m	35 m	25 m
<b>13 mm</b> (M34)	480 m	120 m	60 m	1 170 m	290 m	150 m	250 m	60 m	30 m
<b>19 mm</b> (M34)	710 m	180 m	90 m	1 710 m	430 m	210 m	370 m	90 m	50 m
<b>25 mm</b> (M34)	930 m	230 m	120 m	2 250 m	560 m	280 m	490 m	120 m	60 m
<b>35 mm</b> (M34)	1 300 m	330 m	160 m	3 160 m	790 m	390 m	690 m	170 m	90 m
<b>50 mm</b> (M34)	1 860 m	470 m	230 m	4 510 m	1 130 m	560 m	980 m	250 m	120 m
<b>60 mm</b> (M34)	2 240 m	560 m	280 m	5 410 m	1 350 m	680 m	1 180 m	290 m	150 m
<b>73 mm</b> (M34)	2 720 m	680 m	340 m	6 580 m	1 650 m	820 m	1 430 m	360 m	180 m
<b>100 mm</b> (M34)	3 730 m	930 m	470 m	9 020 m	2 250 m	1 130 m	1 960 m	490 m	250 m

\* Real values may vary based on environmental conditions and integration.



# Contact information

WORKSWELL IN THE WORLD



## Find our partners worldwide

[www.workswell.eu/where-to-buy](http://www.workswell.eu/where-to-buy)

### SALES DEPARTMENT

Website: [www.workswell.eu](http://www.workswell.eu)

E-mail: [sales@workswell.eu](mailto:sales@workswell.eu)

Mobile: +420 737 547 622

### COMPANY CONTACT

Website: [www.workswell.eu](http://www.workswell.eu)

E-mail: [info@workswell.eu](mailto:info@workswell.eu)

Mobile: +420 725 877 063

### OFFICE LOCATIONS

Europe - Prague

United States of America

Global partner network



[www.workswell.eu](http://www.workswell.eu)